

Safe and dynamic standing training  
even for non-standing patients

# balo 536



**THERA-soft®**  
connectable+ 

#### THERA-Trainer balo 536

Item no.	A001-494
----------	----------

● = Equipment variant ○ = Accessory

Name	Item no.	Equipment
Base unit	A002-308	●
Forefoot quick securing system	A002-345	●
Quick securing system for heels	A002-346	●
Balance unit long with low spring resistance	A002-926	●
Knee support set wide	A002-347	●
Pelvic support set	A002-350	●
Table unit with long vertical pipe	A002-310	●
Tread extension connection part, magnetic	A004-915	○
Tread extension mid part, magnetic	A004-916	○
Tread extension ramp, magnetic	A004-917	○
Tread extension set including ramp, magnetic	A004-273	○
Tread enhancement	A002-765	○
Knee support set	A002-671	○
Centre pad for pelvic support set	A003-726	○
Patient belt with bottomenlarged and leg straps,size S/M	A002-352/A002-353	○
Patient belt with bottomenlarged and leg straps,size L/XL	A002-354/A002-355	○
Arm support cushion	A002-428	○
Upper body support	A002-356	○
Center cushions for upper body support	A002-357	○
Electric lift system 230 V/115 V	A002-358/A002-437	○
THERA-soft	A006-630	○
Media station	A008-119	○
Feedback sensor type A including touch button	A003-881	○
Feedback sensor fixing set	A003-977	○

Safe and dynamic standing training  
even for non-standing patients

# balo 536

Product specifications	
<b>Product description</b>	THERA-Trainer balo is a non-powered training device that provides a safe environment to train standing and balancing (postural control) and generally redevelop muscles
<b>Special product features</b>	<ul style="list-style-type: none"> <li>- <b>Two training devices in one:</b> Enables task-oriented, dynamic and safe training of postural control (dynamic training) as well as fast and easy verticalisation (rigid standing training). Also for patients who are not able to stand.</li> <li>- <b>Training postural control in a fall-safe environment:</b> Postural control forms the basis of all day-to-day activities. This central concern (rehabilitation) can be trained effectively through repetitive training at the performance limit. No risk of falling as the body is secured in a standing position.</li> <li>- <b>Quick and easy cleaning:</b> Thorough wipe disinfection is possible thanks to smooth surfaces.</li> <li>- <b>Adjustable without tools:</b> Easily and individually adaptable to each user.</li> <li>- <b>Forward-looking treatment:</b> The THERA-trainer balo can be integrated into a THERA-Trainer complete solution at any time.</li> </ul>
<b>Place of use</b>	Suitable for use in enclosed spaces in facilities e.g. clinics, nursing homes, therapy practices or at the patient's home
<b>Technical specification</b>	<ul style="list-style-type: none"> <li>- <b>Dimensions (LxWxH):</b> 118 cm x 78 cm x 95 - 125 cm if mobile holder for control and display unit used, additional: 77 cm x 70 cm x 130-158 cm</li> <li>- <b>Weight:</b> approx. 77 kg if mobile holder incl. control and display unit used, additional approx. 39 kg</li> <li>- <b>Ambient conditions when in use:</b> Temperature: 5 °C to 40 °C Relative humidity: 5 % to 93 % Rh Air pressure: 700 hPa to 1060 hPa</li> <li>- <b>Sound emission:</b> LpA &lt; 45 dB (A)</li> <li>- <b>Technical details of the electric lift system:</b> Power supply: 230 V~, 50/60 Hz Fuse protection: 2 x 2A slow-acting Protection class: II Degree of protection: Type BF Protection category: IP2X</li> <li>- <b>Service life:</b> 10 years</li> </ul>
<b>Compatibility</b>	THERA-soft
<b>Patient requirements</b>	<ul style="list-style-type: none"> <li>- <b>Patient weight:</b> max. 140 kg</li> <li>- <b>Patient height balance unit:</b> 150 - 200 cm</li> </ul>
<b>Delivery and commissioning</b>	<ul style="list-style-type: none"> <li>- <b>Packaging (LxWxH):</b> 120 cm x 80 cm x 120 cm if mobile holder for control and display unit used, additional: 80 cm x 80 cm x 115 cm</li> <li>- <b>Delivery:</b> Shipping pallets</li> <li>- <b>Transport and storage conditions:</b> Temperature: -25 °C to 70 °C Relative humidity: 5 % to 93 % Rh Air pressure: 700 hPa to 1060 hPa</li> <li>- <b>Commissioning:</b> by authorised specialists</li> </ul>
<b>Service/Maintenance</b>	<ul style="list-style-type: none"> <li>- <b>Service:</b> only by authorised service technicians</li> <li>- <b>Maintenance:</b> Balance unit: Replace after 5 years</li> <li>- <b>Technical inspection:</b> safety inspection every 24 months (manufacturer recommendation)</li> </ul>
<b>Registration</b>	Medical device class: I CE marking: CE